



Premium Archival Matte Paper

LexJet Premium Archival Matte Paper is a 230 g, 9.5 mil, heavy weight, neutral white, matte paper engineered for accurate color reproduction with high contrast and high resolution images. This paper is acid-free, making it the perfect choice for photo reproductions. It is compatible with thermal and piezo ink jet printer platforms as well as with dye and pigment-based ink sets.

Property	Specifications
Material	9.5 mil, 61# matte, neutral white paper
Weight	230 g/m2
Opacity	> 98%
Gloss Level	2% (@ 60°)
Brightness	95
Printer/Ink Compatibility	Encad, ColorSpan, Hewlett-Packard DesignJet, EPSON Series, Roland Series printers with dye & pigmented ink.
Software Setting	The bond or uncoated paper setting in most RIPs is appropriate. However, we recommend that you try a few different settings to achieve optimum performance for your specific application.
Light Fastness	The fading time of ink jet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. All dye-based inks fade noticeably under direct sunlight, in interior applications where direct sunlight may fall on an image, and/or where fluorescent or other UV lighting is present. Although the fading process is inherent with all ink jet inks, certain UV enhanced inks, pigment-based inks, and UV inhibiting laminates will extend the longevity of an image. Contact the ink manufacturer to determine suitability for a particular application.
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying the laminate is not recommended. Thermal laminates can be used on this paper.
Optimal Service Environment	For printing: 72° F, 50% Relative Humidity. For end use: 0-300° F
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface of the paper. It is always recommended that cotton gloves be used when handling ink jet coated materials. Rolls of LexJetpaper and film are supplied with the coated side facing out.
Ideal Storage Conditions	70°F (21°C); 50% R.H.; A controlled environment is recommended; Store in original packaging.
Shelf Life	Greater than 1 year from the LexJet ship date when stored in proper conditions.

Product Performance & Suitability: All of the descriptive information and recommendations for the use of LexJet products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by LexJet. All purchasers of LexJet products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (Including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.